



DESCRIPTION

- POS thermal printer, 32 column.
- RS232 serial port.
- Clock/calendar.
- Paper end sensor.
- Barcode printing in CODE39 format.
- The printer can store an image to use for customizing receipts (software included).
- Scope of delivery: printer, RS232 cable, programming cable, 110/240 VCA power supply, CD-ROM.

TECHNICAL FEATURES

| | |
|---------------------|---------------------------|
| Power supply | 7.5 VDC; 2A |
| Dimensions | 122x93x150 mm |
| Resolution | 8 dots/mm - 384 dots/line |
| Paper width | 57 ±0.5 mm |
| Paper roll diameter | max 60 mm |
| Serial ports | RS232 |
| Net weight | 400 g |
| Gross weight | 950 g |
| Operating humidity | 10% - 80% |
| Working temperature | 0 °C +50 °C |
| Storage temperature | -20 °C +60 °C |

OPTIONS ON REQUEST

| | DESCRIPTION | CODE |
|--|--|---------------|
| | Thermal paper roll for weight/price/amount scales. | CARTAFISC |
| | Thermal paper roll. | CARTASTAVT |
| | Thermal adhesive paper roll. | CARTAFISCADEN |

The Company reserves the right to make changes to the technical data, drawings and images without notice.